



Русский English

- About
- News
- Canopies
- Equipment
- Accessories
- Service
- Prices
- Dealers
- Links



new

canopies

photogallery

- Skipper
- Magellan
- Odyssey
- Commodore
- Recommendations
- Order forms
- Stock Canopies
- Instructions (zip)



Skipper
 Skipper - modern 7-cell versatile
 main Ram-Air Canopy

Skipper offers:

- soft and consistent openings
- easy and safe controls
- moderate descend and sufficient horizontal speed
- high stability in turbulent air
- good flare
- low packing volume

Remarkable performance data were achieved due to use of the original in it's class technological solutions:


- high, as for 7-cell, aspect ratio
- planform similar to that of 9-cell canopies
- special design of air intakes, that reduces deformation of the skin

Our contacts:
 04128, Ukraine, Kyiv,
 26B Boryspilsky Str
 tel./fax: (38044) 566 0142
 info@skylark.com.ua

With wing loadings of 1.3 or below Skipper can be recommended to the beginners. At higher loadings it becomes notably more responsive on the toggles, but stays docile enough for a skydiver of average skills. Skipper gives consistently stable and comfortable openings, sought by cameramen and wingsuit pilots.



Recommended wing loading range of Skipper is 1.1 – 1.7 lb/sq.ft. Wing loading for the best flight performance lies in the range of 1.3 – 1.5 lb/sq.ft.



Skipper is made of ZP fabric in following sizes 110, 120, 130, 140, 150, 160, 170 and 190 sq.ft. The canopy is equipped with Vectran lines, manufacturer preset control lines, collapsible slider with stainless grommets and comes with the set of soft links.



Model / area	Retail Price USD exlude VAT	Packing Volume (cu.in)	Weight, lbs (kg)	Max. Suspended Weight, lbs (kg)
SK-110	1297	289	6 (3)	187 (85)
SK-120	1310	304	6 (3)	204 (93)
SK-130	1322	320	7 (3)	221 (100)
SK-140	1334	336	7 (3)	238 (108)
SK-150	1345	351	7 (3)	255 (116)
SK-160	1356	367	7 (3)	272 (123)
SK-170	1366	382	8 (4)	289 (131)
SK-190	1387	414	8 (4)	300 (136)

We recommend to use our canopies only with kill-line pilot chute, made of ZP fabric and no more than 700mm in diameter. Recommended riser length is 500 mm. Recommended packing is ProPack.

Any use of texts, photos, order forms and their fragments without the written approval of owner TM SKYLARK is forbidden!

