



FIELD REPLACEMENT FOR CUTAWAY HANDLE

CUTAWAY CABLES FITTED TO ICONS
ARE TRIMMED AS DESCRIBED BELOW:

ICON FITTED WITH RSL OR SKYHOOK:

INSERT CABLE INTO HOUSINGS AND PLACE HANDLE IN POCKET. MEASUREMENTS ARE PERFORMED WITH RISERS INSTALLED. RSL SIDE TO MEASURE IS 7.5" / 19.0 CM. NON-RSL SIDE TO MEASURE IS 6.5" / 16.5 CM. MEASUREMENTS TO BE TAKEN FROM HOUSING OPENING TO END OF CABLE. CUT CABLE AND HEAT END TO COVER END OF CABLE WITH YELLOW CABLE CASING.

ICON WITH STRAIGHT PIN NON RSL / NON SKYHOOK:

INSERT CABLE INTO HOUSINGS AND PLACE HANDLE IN POCKET. MEASUREMENTS ARE PERFORMED WITH RISERS INSTALLED. BOTH SIDES TO MEASURE IS 7.0" / 17.8 CM. MEASUREMENTS TO BE TAKEN FROM HOUSING OPENING TO END OF CABLE. CUT CABLE AND HEAT END TO COVER END OF CABLE WITH YELLOW CABLE CASING.

tolerances 1/8" / $\pm 3\text{mm}$