



FIELD REPLACEMENT FOR

# CUTAWAY HANDLE

CUTAWAY CABLES FITTED TO ICONS  
ARE TRIMMED AS DESCRIBED BELOW:

## **ICON FITTED WITH RSL OR SKYHOOK:**

INSERT CABLE INTO HOUSINGS AND PLACE HANDLE IN POCKET. MEASUREMENTS ARE PERFORMED WITH RISERS INSTALLED. RSL SIDE TO MEASURE IS 7.5" / 19.0 CM. NON-RSL SIDE TO MEASURE IS 6.5" / 16.5 CM. MEASUREMENTS TO BE TAKEN FROM HOUSING OPENING TO END OF CABLE. CUT CABLE AND HEAT END TO COVER END OF CABLE WITH YELLOW CABLE CASING.

---

## **ICON WITH STRAIGHT PIN NON RSL / NON SKYHOOK:**

INSERT CABLE INTO HOUSINGS AND PLACE HANDLE IN POCKET. MEASUREMENTS ARE PERFORMED WITH RISERS INSTALLED. BOTH SIDES TO MEASURE IS 7.0" / 17.8 CM. MEASUREMENTS TO BE TAKEN FROM HOUSING OPENING TO END OF CABLE. CUT CABLE AND HEAT END TO COVER END OF CABLE WITH YELLOW CABLE CASING.

tolerances 1/8" /  $\pm 3\text{mm}$